


GLT-D100B

產品結構Structure



技術參數 Technical Data

項目 Item	單位 unit	規格值 Spec.
基材厚度 Thickness	μm	4.5 ±1
鍍層厚度 (Inside)Thickness	μm	1 ±0.3
鍍層厚度 (outside)Thickness	μm	1 ±0.3
產品總厚 Total Thickness	μm	6.5 ± 1.0
鍍層附着強度 peeling strength	%	100
拉伸率 Elongation	%	> 3
抗張強度(MD) Tensile strength Transverse at RT (MD)	MPa	> 150
抗張強度(TD) Tensile strength Transverse at RT (TD)	MPa	> 150
粗糙度Ra(內層) In side Roughness(Ra)	μm	< 0.5
粗糙度Rz(內層) In side Roughness(Rz)	μm	< 2.0
粗糙度Ra(外層) Outside Roughness(Ra)	μm	< 0.5
粗糙度Rz(外層) Outside Roughness(Rz)	μm	< 2.0
面電阻(內層) In side Resistivity	mΩ/□	< 30
抗氧化性 Antioxidant properties	120°C/15min	外觀無明顯變化 no significant change in appearance

*以上產品數據為我司實驗室測試, 僅供貴司參考

*The above product data is our laboratory test and is for your reference only.

環保測試 Environmental

符合RoHS 與歐盟無鹵標準

RoHS compliant and EU halogen-free